



Powder Tester (PT2C)

With the OCS Powder Tester (PT2C), powdery materials can be analysed on a vibration plate using a colour matrix camera. The system detects impurities that show a colour deviation from the product. An additional feature of the PT2C is a sorting system (optional) that sorts out the contaminated powder. Further advantages are the data transfer of the real-time results to the production and process control as well as the subsequent evaluation of the sorted-out powder by further analysis systems.

Testable Raw Materials

- Powdery materials (free-flowing)

Features

- High-performance 3CMOS colour matrix camera
- Smallest detectable contamination size: 10 µm
- Throughput rate of up to 1200 g/h depending on the material and resolution
- Visualisation of the real-time results
- Sorting system for sorting out the contaminated powder (optional)

Sales Team



T +49 2302 95622-0
F +49 2302 95622-33
info@ocsmbh.com
www.ocsmbh.com


Address

OCS Optical Control Systems GmbH
Wullener Feld 24
58454 Witten
Germany




Technical Details

Camera	3CMOS colour matrix camera
Resolution	10 µm

Lighting	High-power LED with white light spectrum
Communication protocol	MODBUS (RTU, TCP/IP), PROFIBUS, PROFINET, OPC (Server/Client), CSV file, customer-specific



More Product Pictures



Images, drawings and data are non-binding and subject to modification without prior notice. © 2024. All rights reserved - OCS Optical Control Systems GmbH | Wullener Feld 24 | 58454 Witten, Germany